

BS2752-C70 Neoprene Rubber



DRC27

DATA SHEET

DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

Description

DRC27 Black BS2752-C70 specification high quality Neoprene 70° shore A material, suitable for a wide range of applications with excellent general mechanical properties and resistance to oils & greases, water, ozone, mild chemicals, acids etc.

Technical Information

Material:	Chloroprene BS specification grade
Application:	General Purpose, Water/UV/Oil/Fuel Resistant
Thickness:	0.5,1,1.5,2,3,5,6mm
Colour:	Black
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.40
Hardness [Degrees Shore A]:	70° ± 5°
Tensile Strength [MPa]:	13 min
Elongation at Break:	300%
Minimum Temperature:	-30°C
Maximum Temperature:	+120°C
Compression Set:	25%
Tear Resistance (kg/cm)	N/A

Thickness

0.5mm-6mm
(other thicknesses on request)

Sheet Size

1.4m wide x 5,10m
rolls

Finish

Plate

Cutting

Standard Press Tools

