Red/Pink Natural Abrasion Rubber

DATA SHEET

DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road, Christchurch, Dorset, BH23 4HD t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

Description

This material is the ultimate rubber for high wear & abrasion resistance. Specially compounded from 95% pure natural Latex, this material is recognised as the premium material developed for slurry & abrasive handling applications, chutes & tank linings, pipelines, hydrocyclones and sumps, valves and pumps. A truly exceptional material.

Technical Information

Material:	Red Natural Rubber	
		Т
Application:	High Abrasion Resistance	1
Thickness:	.5,3,5,6,8,10,12,15,20,25mm	1
Colour:	Pink/Red	(Other tl
Cloth/Plate Finish:	Clothe	
Compound:	NR	S
Density [specific gravity]:	.98	1.4m v
Hardness [Degrees Shore A]:	40	
Elongation at break %:	810%	
Minimum Temperature:	-20°C	C
Maximum temperature:	+70°C	
Abrasion resistance (mm3):	N/A	
Tear resistance (kg/cm):	N/A	Stan
Compression Set 70°, 22hrs:	20%	



1.5mm-25mm thickness on request)

Sheet Size wide x 5,10m rolls

> Finish Cloth Marked

Cutting ndard Press Tools



